

Amendments to the Claims

Kindly cancel claims 5 and 9.

Kindly amend claim 1.

1. (Currently amended) Method for production of a CO₂-rich gas stream and a H₂-rich gas stream, characterized in that the method comprises the following steps:

- a) natural gas and water are fed to a reforming reactor and converted to synthesis gas under supply of an O₂-rich gas to the reactor;
- b) the gas stream from a) is shifted, in one step, whereby the content of CO is reduced and the amounts of CO₂ and H₂ are increased by reaction of H₂O at a ratio H₂O:CO of from 1 to 9;
- c) the gas stream from b) is separated in a separation unit into a CO₂-rich and a H₂-rich gas stream, respectively, wherein the pressure in the CO₂-rich gas stream after the separation is from 5 to 100 bar.

2-3. (Previously cancelled)

4. (Previously presented) Method according to claim 1, characterized in that the ratio H₂O:CO in the shift process is from 1.5 to 4.

5. (Cancel)

6. (Previously presented) Method according to claim 1, characterized in that the pressure in the CO₂-rich gas stream after the separation unit is from 5 to 50 bar.

7. (Previously presented) Method according to claim 1,
characterized in that the carbon part in the H₂-rich gas stream is from 1 to 20 % by
volume.

8. (Previously presented) Method according to claim 1,
characterized in that the carbon part in the H₂-rich gas stream is from 5 to 15 % by
volume.

9. (Cancel)

10. (Previously presented) Method according to claim 1,
characterized in that the natural gas in step a) is supplied with air/oxygen enriched air.

11. (Previously presented) Method according to claim 1,
characterized in that the reformer reactor is a partial oxidation reactor.

12. (Previously presented) Method according to claim 1,
characterized in that the reformer reactor is an autothermal reformer.

13. (Original) Method according to claim 12,
characterized in that the gas stream from a combustion chamber in an autothermal
reformer is contacted with a catalyst bed.

14. (Previously presented) Method according to claim 11,
characterized in that the reforming is carried out without a catalyst.

15. (Previously presented) Method according to claim 1,
c h a r a c t e r i z e d i n that the gas stream out of the reformer has a temperature within the
interval from 800 to 1200°C.

16. (Previously presented) Method according to claim 10,
c h a r a c t e r i z e d i n that the CO₂-rich gas stream includes at least part of N₂.

17. (Previously presented) Method according to claim 1 wherein the produced
CO₂-rich gas stream is applied for injection into marine formations.

18. (Previously presented) Method according to claim 1 wherein the produced H₂-
rich gas stream is applied for hydrogenation.

19. (Previously presented) Method according to claim 1 wherein the produced H₂-
rich gas stream is applied as a source of energy / fuel in fuel cells.

20. (Previously presented) Method according to claim 1 wherein the produced H₂-
rich gas stream is applied for the production of electricity.